



(PUR) POP UP RECEPTACLE INSTALLATION INSTRUCTIONS

FOR CATALOG NUMBERS: PUR20-B; PUR20-BK; PUR20-OW; PUR20-S; PUR15-B; PUR15-BK; PUR15-OW; PUR15-S; PUR15-BK-2P; PUR15-S-2P

IMPORTANT: Read all instructions before installing the PUR SERIES

PRIOR TO INSTALLATION

- Contact a local electrical inspector to make sure that this product meets or exceeds all local electrical codes (electric codes may vary by location).
- Make sure there is adequate space to install (see below: *CUT OUT AND MOUNTING STEPS*)
- Disconnect and turn off all power sources.
- All non GFI units must be wired to a GFCI circuit breaker if being installed in a kitchen, bathroom, or any other area that the potential for water is present.

CONDITIONS:

- For indoor use only.
- This product is designed for countertops, desktops, and similar surfaces (this product is not suitable for floor use).
- Only licensed, insured, and bonded electrical contractors should install the PUR series.
- These products have no field serviceable parts. If the product is damaged, it must be returned to the factory. Any attempt to alter this product in any way may cause electrocution.

CUTOUT AND MOUNTING STEPS

- Select the desired location of the countertop or desktop at least 10" from stove top or other heating sources.
- The selected location must be at least 20mm (13/16") away from the edge of the countertop or similar surface.
- The mounting surface must be between 9.5mm (3/8") and 55mm (2 3/16") thick and have the below clearances:

PUR15 style:

In use height: 6 1/4" (159 mm)

Non use depth under counter: 9 1/4" (235 mm)

PUR20 style:

In use: 5 5/8" (143 mm)

Non use: 8 1/2" (216 mm)

PUR15-2P, PUR-2P, PUR20-2P:

In use: 10 3/4" (273 mm)

Non use: 13 3/4" (349 mm)

SEE BACKSIDE FOR REST OF INSTRUCTIONS



Outlet box must be installed underneath the countertop by a licensed and electrician.

- 1. Cut hole in surface of countertop 95.25 mm (3.75").*
- 2. Remove plastic threaded locking flange from PUR unit.*
- 3. Feed power cord through hole in countertop first, followed by PUR unit, pushing down until black gasket resting on countertop.*
- 4. Feed power cord through plastic locking flange and thread flange counterclockwise until locked in place against back of countertop.*
- 5. Plug power cord into electrical outlet box underneath countertop.*
- 6. Remove plastic protective film from cover and discard.*
- 7. To open pop up feature, press firmly on cover. Unit will deploy upward approximately 1" initially, then pull cover upward until unit locks into place.*
- 8. To close device, push the red plastic locking tab and push down on cover until unit locks.*

NOTE: Countertop unit must be cut in as specified. In order for unit to deploy, the metal flange and black neoprene gasket must be on top of countertop to create counter pressure. Attempting to cut a larger hole to draw down the cover closer to the countertop will not allow the cover to deploy as there is not enough counter pressure to make the unit release. There will be a 3/16" gap when cover is closed, however, the watertight rating will still be valid as no liquid or solid can penetrate the gasket. A matching outer flange trim rings ships with every PUR, it can be installed to provide a more contoured look with the countertop. However, this look is personal preference, you may like the look with or without it. If you wish to install, place a small bead of silicone on the bottom of the ring, then place on counter around pop up and allow 24 hours to dry. All non GFI PUR units include a reset button at the top of the units. The PUR series is under manufacturer warranty for one year from date of purchase.

For further instruction, please visit our website at www.lewelectric.com to see video of these types of units installed. Or, use your smartphone to read the QR code from the label on these devices.